

# High-Powered ELCs

## LECI Series



Our higher-powered ELCs offer an unparalleled flexibility to meet your needs. With two different amprated units (40A and 60A) and a wide variety of operating voltages (120/208/240/480/600), There is a unit that will work for you.

Trip levels are selectable on the unit to offer the maximum protection while minimizing nuisance tripping. Automatic and manual reset modes are also selectable on the unit.

**Approvals:** cCSAus Certified

- Frequency: 60Hz
- Response Time: 25mS max at 500 ohm fault
- Operating Temperature: -35°C to 66°C
- Reset Type: Field selectable – automatic or manual reset
- Enclosure: NEMA 4X wet location rated
- Switching Interface: Double insulated and recessed

Part Number	Volts/Amp	Cord Line & Load	Phase	Trip Levels
LECI-601201	120V/60A	6' of 6/3 SOOW cable	1 $\emptyset$	6/10/30mA
LECI-402401	240V/40A	6' of 8/3 SOOW cable	1 $\emptyset$	6/10/30mA
LECI-402083	208V/40A	2' of 10/4 SOOW cable	3 $\emptyset$	6/10/30mA
LECI-402403	240V/40A	2' of 10/4 SOOW cable	3 $\emptyset$	6/10/30mA
LECI-602083	208V/60A	6' of 6/4 SOOW cable	3 $\emptyset$	6/10/30mA
LECI-602403	240V/60A	6' of 6/4 SOOW cable	3 $\emptyset$	6/10/30mA
LECI-404803	480V/40A	6' of 6/4 SOOW cable	3 $\emptyset$	6/10/30mA
LECI-604803	480V/60A	6' of 6/4 SOOW cable	3 $\emptyset$	6/10/30mA
LECI-606003	600V/60A	2' of 6/4 SOOW cable	3 $\emptyset$	6/10/30mA