


LIND EQUIPMENT

Transformer Cart



Lind Equipment's portable Transformer Cart is innovatively designed to allow for **quick and convenient access to electrical components**, while still maintaining a high level of **safety and portability**. The compact design allows this cart to **fit through standard sized doors**, making it easy to move from one space to another as needed.

Built to withstand the toughest environments, and constructed with a powder coated steel frame, Lind's portable Transformer Cart will last for many projects to come.



Features

- Accommodates 30-75KVA transformers
- Forklift/ telehandler pockets
- Hoisting eyelets
- Heavy duty swivel casters
- Covered storage shelf
- Weatherproof electrical enclosures
- USB-A charging receptacle
- Built-in Beacon360 area light

Benefits

- Multiple input options
- Fits through standard sized man doors
- Seamless compatibility with other Lind products
- Easy to maintain and source components
- Custom powder coat colours (optional)
- Plasma etched company logo in frame (optional)

An innovative take on traditional portable power and the smartest way to power your jobsite.

LIND EQUIPMENT

Transformer Cart

Specifications

Part Numbers	LE-45TC600208-60 (600V) LE-45TC480208-60 (480V)	LE-45TC600208-100 (600V) LE-45TC480208-100 (480V)	LE-75TC600208-100 (600V) LE-75TC480208-100 (480V)	LE-75TC600208-200 (600V) LE-75TC480208-200 (480V)
Input	60A	100A	100A	200A
Primary Voltage (600V or 480V)	60A Disconnect Switch (Fused or Non- Fused)	100A Main Breaker 60A Breaker to Transformer 4x 20A 277V Breakers	100A Disconnect Switch (Fused or Non- Fused)	200A Main Breaker 100A Breaker to Transformer 2x 50A 480V Twist Lock (Non-NEMA)
Transformer	45KVA		75 KVA	
Secondary Voltage (120/208V)	150A Main Breaker 4x 50A 125/250V Twist Lock (California Std) 6x 20A 125V T-Slot GFCI Duplex (5-20R) 2x 30A 250V Twist Lock (L6-30R) 1x 4.8A 125V USB-A (Quad)		225A Main Breaker 6x 50A 125/250V Twist Lock (California Std) 6x 20A 125V T-Slot GFCI Duplex (5-20R) 2x 30A 250V Twist Lock (L6-30R) 1x 4.8A 125V USB-A (Quad)	
Dimensions	55.5" L x 30.75" W x 67.5" H			
Enclosure Rating	NEMA 3R			
Construction	Heavy Gauge Powder Coated Steel			
Package Recommendation	45 KVA 1x 45KVA Transformer Cart 4x 92000 (Spider Boxes) 4x 91007 (100ft cords for Spider Boxes) Total Coverage= 50,000ft ²		75 KVA 1x 75KVA Transformer Cart 6x 92000 (Spider Boxes) 6x 91007 (100ft cords for Spider Boxes) Total Coverage= 70,000ft ²	

If our standard configurations aren't exactly what you're looking for, Lind's Transformer Cart can be customized to meet your project's unique specifications. Contact your local representative to discuss your project requirements in further detail.

Package recommendation assumptions

- Each 50A circuit is powering one (1) Spider Box
- Each unit is paired with 50ft extensions cords, amounting to a 100ft x 100ft area of coverage (10,000ft²)